



This is to certify that: The Parkside Group Ltd

Units 5

The Willow Centre 17 Willow Lane

Mitcham Surrey CR4 4NX

United Kingdom

Holds Certificate Number: KM 578160

In respect of:

BS 4873 / PAS24 Enhanced Security Aluminium Window System Supplier

This issues the right and licence to use the Kitemark in accordance with the Kitemark Terms and Conditions governing the use of the Kitemark, as may be updated from time to time by BSI Assurance UK Ltd (the "Conditions"). All defined terms in this Certificate shall have the same meaning as in the Conditions.

The use of the Kitemark is authorized in respect of the Product(s) detailed on this Certificate provided at or from the above address.

For and on behalf of BSI: Chris Lewis - Certification Director, Product Certification

First Issued: 2012-03-16 Effective Date: 2017-11-08 Latest Issue: 2017-11-08 Expiry Date: 2020-11-07

Page: 1 of 11

...making excellence a habit.™



No. KM 578160

BS 4873:2016 / PAS 24:2016 - Enhanced security performance requirements for window assemblies.

This Certificate covers the following window system design specification. Only those components that have been approved in accordance with the Kitemark scheme requirements can be incorporated within the system(s) detailed.

System(s): Comar 5Pi Aluminium Alloy Window System

Fabrication and Installation:

Fabricated and installed in accordance with the latest issue(s) of the following

Comar Architectural Aluminium Systems controlled documentation:

Comar 5Pi Window System Technical Manual Comar 5Pi Enhanced Security Document

System description: The windows are internally glazed only, double glazed only, multipoint locking

only with mechanically fixed transoms/mullions

Ventilation: None

Window Types: Tilt/turn windows - Comar Security Hardware

Multilight windows comprising opening light(s) and/or fixed light(s)

Page: 2 of 11

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.

No. KM 578160

Comar 5Pi Aluminium Alloy Window System Size Limitations and Performance characteristics

Window Type	Width (mm) - Maximum	Height (mm) - Maximum	Area(m²) - Maximum	Transom/Mullion Length (mm) inc frame - Maximum	Air Permeability classification	Watertightness classification	Resistance to Wind classification	Exposure category as given in Table 1 of BS 6375-1:2009 (except*)
Sash dimensions for appr	oved tilt/t	urn sash p	orofiles:					
Tilt/turns	1100	1600	-	-	4	7A	2400	2400*
Overall dimensions for approved outer frames & transom/mullion profiles:								
Multilight Tilt & Turn CS 435 Mullion	1200	1600	-	1550	4	5A	A5	2000

^{*}as given in Table 1 of BS 6375-1:2004

First Issued: 2012-03-16 Effective Date: 2017-11-08 Latest Issue: 2017-11-08 Expiry Date: 2020-11-07

Page: 3 of 11

No. KM 578160

BS 4873:2016 / PAS 24:2016 - Enhanced security performance requirements for window assemblies.

This Certificate covers the following window system design specification. Only those components that have been approved in accordance with the Kitemark scheme requirements can be incorporated within the system(s) detailed.

System(s): Comar 5Pi Advanced Aluminium Alloy Window System

Fabrication and Installation:

Fabricated and installed in accordance with the latest issue(s) of the following

Comar Architectural Aluminium Systems controlled documentation:

Comar 5Pi Advanced Window System Technical Manual

Comar 5Pi Advanced Enhanced Security Document

System description: The windows are internally glazed only, double glazed only, multipoint locking

only with mechanically fixed transoms/mullions

Ventilation: None

Window Types: Casement windows - Kenrick espagnolette system operated by a key locking

handle and Sterling hinge

First Issued: 2012-03-16 Effective Date: 2017-11-08

Latest Issue: 2017-11-08 Expiry Date: 2020-11-07

Page: 4 of 11

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.

No. KM 578160

Comar 5Pi Advanced Aluminium Alloy Window System Size Limitations and Performance characteristics

Window Type	Width (mm) - Maximum	Height (mm) - Maximum	Area(m²) - Maximum	Transom/Mullion Length (mm) inc frame - Maximum	Air Permeability classification	Watertightness classification	Resistance to Wind classification	Exposure category as given in Table 1 of BS 6375-1:2009	
Sash dimensions for approved tilt/turn sash profiles:									
Projecting top hungs	1180	1430	-	-	4	9A	A5	2000	

First Issued: 2012-03-16 Effective Date: 2017-11-08 Latest Issue: 2017-11-08 Expiry Date: 2020-11-07

Page: 5 of 11

No. KM 578160

BS 4873:2016 / PAS 24:2016 - Enhanced security performance requirements for window assemblies.

This Certificate covers the following window system design specification. Only those components that have been approved in accordance with the Kitemark scheme requirements can be incorporated within the system(s) detailed.

System(s): Comar 5Pi ECO 55/75 Aluminium Alloy Window System

Fabrication and Installation:

Fabricated and installed in accordance with the latest issue(s) of the following

Comar Architectural Aluminium Systems controlled documentation:

Comar 5Pi ECO Window System Technical Manual

Comar 5Pi ECO Enhanced Security Document

System description: The windows are internally glazed only, double glazed only, multipoint locking

only with mechanically fixed transoms/mullions

Ventilation: None

Window Types: Casement windows - Comar Security Hardware

Multilight windows comprising opening light(s) and/or fixed light(s)

First Issued: 2012-03-16 Effective Date: 2017-11-08 Latest Issue: 2017-11-08 Expiry Date: 2020-11-07

Page: 6 of 11

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.

No. KM 578160

Comar 5Pi ECO 55/75 Aluminium Alloy Window System **Size Limitations and Performance Characteristics**

Window Type	Width (mm) - Maximum	Height (mm) - Maximum	Area (m²) - Maximum	Transom/Mullion Length (mm) inc frame - Maximum	Air Permeability classification	Watertightness classification	Resistance to Wind classification	Exposure category as given in Table 1 of BS 6375-1:2009 (except*)
Sash dimensions for app	proved cas	sement s	sash pro	files:			1	
Projecting top hungs	1100	1116	-	-	4	7A	2400	2400*
Overall dimensions for a	pproved o	outer fra	mes & tı	ransom/mu	llion profil	es:		
Multilight Projecting side hung next to Projecting side hung Mullion CS 835	1305	1330	-	1270	2	E750	AE	2400
Multilight Projecting side hung next to Fixed Mullion CS 835	1300	1320	-	1235	4	E600	E2400	2400

^{*}as given in Table 1 of BS 6375-1:2004

First Issued: 2012-03-16 Effective Date: 2017-11-08 Latest Issue: 2017-11-08 Expiry Date: 2020-11-07

Page: 7 of 11

No. KM 578160

BS 4873:2016 / PAS 24:2016 - Enhanced security performance requirements for window assemblies.

This Certificate covers the following window system design specification. Only those components that have been approved in accordance with the Kitemark scheme requirements can be incorporated within the system(s) detailed.

System(s): Comar 5Pi ECO+ Aluminium Alloy Window System

Fabrication and Installation:

Fabricated and installed in accordance with the latest issue(s) of the following

Comar Architectural Aluminium Systems controlled documentation:

Comar 5Pi ECO+ Window System Technical Manual

Comar 5Pi ECO+ Enhanced Security Document

System description: The windows are internally glazed only, double glazed only, with mechanically fixed transport from the strength of the s

fixed transoms/mullions. Locking mechanism ERA (LK5846XKIT) and

hinges Securistyle (HN806XSLF).

Ventilation: None

Window Types: Casement windows

Page: 8 of 11

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.

No. KM 578160

Comar 5Pi ECO+ Aluminium Alloy Window System **Size Limitations and Performance Characteristics**

Window Type	Width (mm) - Maximum	Height (mm) - Maximum	Area (m²) - Maximum	Transom/Mullion Length (mm) inc frame - Maximum	Air Permeability classification	Watertightness classification	Resistance to Wind classification	Exposure category as given in Table 1 of BS 6375-1:2009
Sash dimensions for approved casement sash profiles:								
Projecting top hungs	1152	1152	-	-	4	E750	2400	2400

First Issued: 2012-03-16 Effective Date: 2017-11-08 Latest Issue: 2017-11-08 Expiry Date: 2020-11-07

Page: 9 of 11

No. KM 578160

BS 4873:2016 / PAS 24:2016 - Enhanced security performance requirements for window assemblies.

This Certificate covers the following window system design specification. Only those components that have been approved in accordance with the Kitemark scheme requirements can be incorporated within the system(s) detailed.

System(s): Comar 9Pi Aluminium Alloy Window System

Fabrication and Installation:

Fabricated and installed in accordance with the latest issue(s) of the following

Comar Architectural Aluminium Systems controlled documentation:

Comar 9Pi Window System Technical Manual

Comar 9Pi Enhanced Security Document

System description: The windows are internally glazed only, double glazed only, multipoint locking

only with mechanically fixed transoms/mullions

Ventilation: None

Window Types: Casement windows - Giesse locking system operated by a key locking handle

and Giesse hinges or Winlock locking system operated by a key locking handle

and Sterling hinges

Tilt/turn windows - Giesse T/T locking system operated by a key locking handle and T/T Giesse hinges or Sobinco T/T gearing operated by a key locking handle

First Issued: 2012-03-16 Effective Date: 2017-11-08

Latest Issue: 2017-11-08 Expiry Date: 2020-11-07

Page: 10 of 11

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.

No. KM 578160

Comar 9Pi Aluminium Alloy Window System Size Limitations and Performance characteristics

Window Type	Width (mm) - Maximum	Height (mm) - Maximum	Area(m²) - Maximum	Transom/Mullion Length (mm) inc frame - Maximum	Air Permeability classification	Watertightness classification	Resistance to Wind classification	Exposure category as given in Table 1 of BS 6375-1:2009	
Sash dimensions for appr	oved case	ment sasl	n profiles:						
Projecting top hungs	995	1595	-	-	4	E900	A5	2000	
Projecting side hungs	1180	1440	-	-	4	9A	AE	2400	
Overall dimensions for approved outer frames & transom/mullion profiles:									
Tilt/turns	1180	1440	-	-	4	9A	AE	2400	
Tilt/turns	1040	1650	-	-	4	E750	A5	2000	

First Issued: 2012-03-16 Effective Date: 2017-11-08 Latest Issue: 2017-11-08 Expiry Date: 2020-11-07

Page: 11 of 11